

are being manufactured in compliance with the requirements of this specification and with the manufacturer's plans and specifications approved by the Commandant.

(b) *Methods of test*—(1) *Waterproof test*. The searchlight shall be subjected for 5 minutes to a stream of water under a head of approximately 35 feet from a hose not less than 1 inch in diameter from a distance of approximately 10 feet. The hose nozzle shall be adjusted to give a solid stream at the enclosure. No leakage shall occur in this test.

(2) *Beam candlepower*. All light except that produced from the searchlight under test shall be excluded from the room in which measurements are made. The searchlight shall be operated at rated voltage with a seasoned lamp as specified in § 161.006-4(e). Measurements of beam candlepower shall be made at the corners of a 6-inch square located in the center of the beam at a distance of 32 feet immediately in front of the searchlight.

(3) *Corrosion resistance*. The searchlight shall be subjected to a 200-hour salt spray test in accordance with ASTM B 117 (incorporated by reference, see § 161.006-1). There shall be no evidence of corrosion that will be detrimental to the operation of the searchlight.

(4) *Heat run*. The searchlight, completely assembled, shall be operated continuously for 2 hours at rated voltage following which the waterproof test shall be conducted. This cycle shall be repeated 3 times. The ambient temperature shall be approximately 25 °C. The water stream shall be from an ordinary cold water tap.

CGFR 49-43, 15 FR 127, Jan. 11, 1950, as amended by USCG-1999-5151, 64 FR 67185, Dec. 1, 1999]

#### § 161.006-6 Procedure for approval.

(a) *General*. Motor lifeboat searchlights are approved only by the Commandant, United States Coast Guard, Washington, DC, 20226. Correspondence relating to the subject matter of this specification shall be addressed to the Commander of the Coast Guard District in which the factory is located.

(b) *Manufacturer's plans and specifications*. In order to obtain approval of motor lifeboat searchlights, submit de-

tailed plans and specifications, including a complete bill of material, assembly drawings, and parts drawings descriptive of the arrangement and construction of the device, to the Commander of the Coast Guard District in which the factory is located. Each drawing shall have an identifying drawing number, date, and an identification of the device; and the general arrangement for assembly drawing shall include a list of all drawings applicable, together with drawing numbers and alteration numbers. The manufacturer will be advised whether or not the drawings and specifications appear satisfactory or what corrections appear necessary and then he may proceed with the construction of the pre-approval sample in accordance therewith. The pre-approval sample, together with four copies of the plans and specifications corrected as may be required, shall be forwarded to the Commandant via the Commander of the Coast Guard District in which the factory is located for inspection and tests. The cost of the tests is to be borne by the manufacturer.

#### Subpart 161.008 [Reserved]

#### Subpart 161.010—Floating Electric Waterlight

SOURCE: CGD 85-208, 54 FR 27020, June 27, 1989, unless otherwise noted.

#### § 161.010-1 Incorporation by reference.

(a) Certain materials are incorporated by reference into this part with the approval of the Director of the Federal Register in accordance with 5 U.S.C. 552(a). To enforce any edition other than the one listed in paragraph (b) of this section, notice of change must be published in the FEDERAL REGISTER and the material made available to the public. All approved material is on file at the Office of the Federal Register, 800 North Capitol Street, NW., suite 700, Washington, DC, and at the Commanding Officer, USCG Marine Safety Center, 400 Seventh Street SW., Washington, DC 20590-0001, and is available from the sources indicated in paragraph (b) of this section.

## § 161.010-2

(b) The material approved for incorporation by reference in this part, and the sections affected are:

UNDERWRITERS LABORATORIES, INC.  
12 Laboratory Drive, Research Triangle Park,  
NC 27709-3995

ANSI/UL 1196, Standard for Floating  
Waterlights, Second Edition March 23,  
1987. 161.010-2; 161.010-4

[CGD 85-208, 54 FR 27020, June 27, 1989, as  
amended by CGD 95-072, 60 FR 50467, Sept. 29,  
1995; CGD 96-041, 61 FR 50733, Sept. 27, 1996;  
CGD 97-057, 62 FR 51049, Sept. 30, 1997; USCG  
2001-10224, 66 FR 48620, Sept. 21, 2001]

### § 161.010-2 Design, construction, and test requirements.

Each floating electric waterlight  
shall meet the requirements of ANSI/  
UL 1196.

### § 161.010-3 Inspections and methods of test.

(a) Each inspection and test report  
required by this subpart shall comply  
with § 159.005-11 of this chapter.

(b) The U.S. Coast Guard reserves the  
right to make any inspection or test it  
deems necessary to determine the con-  
formance of the materials and equip-  
ment to this subpart.

(c) The facilities, materials, and  
labor for all tests shall be furnished at  
no cost to the U.S. Coast Guard.

### § 161.010-4 Procedure for approval.

(a) A request for approval of an auto-  
matic floating electric waterlight must  
be submitted to the Commanding Offi-  
cer, USCG Marine Safety Center, 400  
Seventh Street SW., Washington, DC  
20590-0001.

(b) All inspections and tests must be  
performed by an independent labora-  
tory which meets the requirements of  
§ 159.010-3 of this chapter. A list of inde-  
pendent laboratories accepted by the  
Coast Guard as meeting § 159.010-3 of  
this chapter may be obtained by con-  
tacting the Commanding Officer, USCG  
Marine Safety Center.

(c) Each request for approval must  
contain:

(1) The name and address of the ap-  
plicant,

(2) One copy of all plans and speci-  
fications that meet the requirements of  
§ 159.005-12 of this chapter,

## 46 CFR Ch. I (10-1-03 Edition)

(3) A pre-approval sample of the  
waterlight,

(4) An inspection and test report  
verifying compliance with the con-  
struction and test requirements of  
ANSI/UL 1196, and

(5) A statement by the manufacturer  
certifying that the waterlight complies  
with the requirements of this subpart.

[CGD 85-208, 54 FR 27020, June 27, 1989, as  
amended by CGD 95-072, 60 FR 50467, Sept. 29,  
1995; CGD 96-041, 61 FR 50734, Sept. 27, 1996;  
USCG 2001-10224, 66 FR 48620, Sept. 21, 2001]

## Subpart 161.011—Emergency Position Indicating Radiobeacons

### § 161.011-1 Purpose.

This subpart prescribes approval re-  
quirements for emergency position in-  
dicating radiobeacons (EPIRB).

[39 FR 10139, Mar. 18, 1974]

### § 161.011-5 Classes.

EPIRB's are classed as follows:

(a) Class A—an EPIRB that has been  
type approved or type accepted by the  
FCC as a Class A EPIRB. These  
EPIRB's are capable of floating free of  
a vessel and activating automatically  
if the vessel sinks.

(b) Class C—An EPIRB that has been  
type approved or type accepted by the  
FCC as a Class C EPIRB. These  
EPIRB's are manually activated and  
are not required to be Coast Guard ap-  
proved.

[39 FR 10139, Mar. 18, 1974, as amended by  
CGD 80-024, 49 FR 40409, Oct. 16, 1984]

### § 161.011-10 EPIRB approval.

(a) The Coast Guard approves the  
class of EPIRB's listed in § 161.011-5(a)  
of this subpart.

(b) An application for type approval  
or type acceptance of an EPIRB should  
be submitted to the FCC in accordance  
with Title 47 of the Code of Federal  
Regulations, Part 2. When requested by  
the FCC, the Coast Guard reviews the  
test results in the application that con-  
cern installation and automatic oper-  
ation (if required) of the EPIRB. The  
Coast Guard provides the results of the  
review to the manufacturer, and to the  
FCC for its use in acting upon the ap-  
plication.